




## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification <sup>6</sup> : <b>A01G 9/10</b>	<b>A2</b>	(11) International Publication Number: <b>WO 00/00014</b> (43) International Publication Date: 6 January 2000 (06.01.00)
<p>(21) International Application Number: PCT/NL99/00405</p> <p>(22) International Filing Date: 30 June 1999 (30.06.99)</p> <p>(30) Priority Data: 1009527 30 June 1998 (30.06.98) NL</p> <p>(71) Applicant (for all designated States except US): V.O.F. GEBR. SMAK &amp; ZN. [NL/NL]; Grutteweide 7, NL-1693 HR Wervershoof (NL).</p> <p>(72) Inventor; and (75) Inventor/Applicant (for US only): SMAK, Pieter, Wilhelmus, Johannes [NL/NL]; Grutteweide 7, NL-1693 HR Wervershoof (NL).</p> <p>(74) Agent: DE BRUIJN, Leendert, C.; Nederlandsch Octrooibureau, Scheveningsweg 82, P.O. Box 29720, NL-2502 LS The Hague (NL).</p>	<p>(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).</p> <p><b>Published</b> <i>In English translation (filed in Dutch). Without international search report and to be republished upon receipt of that report.</i></p>	

(54) Title: PLANT TRAY AND CULTIVATION SYSTEM PROVIDED WITH SUCH A PLANT TRAY

## (57) Abstract

Plant tray consisting of a plastic body in which a number of accommodations have been made. Viewed in the use position, said accommodations are open both at the bottom and at the top. The plant is inserted at the top and roots, which optionally can be brought into contact with water, are able to develop through the bottom. So as to be able to remove the plant easily and to prevent the roots growing together into a solid mass, it is proposed to construct the boundary of the opening at the bottom in the form of a cutting edge. Clamping means, such as plates extending into the accommodations, can be provided for clamping plants such as bulbs. These plates, and in particular the part that comes into contact with the bulbs, can be made sharp.



**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

Plant tray and cultivation system provided with such a plant tray.

The present invention relates to a plant tray according to the preamble clause of Claim 1.

5 A plant tray of this type is disclosed in EP 0 758 524 A1. Tulip bulbs, but also other plants, are grown in such trays.

Netherlands Laid Open Application 9200641 describes a plant tray wherein the bottom of each of the accommodations is closed. Bulbs are placed in these accommodations through insertion openings made at the top and water is then supplied. This water collects at the  
10 bottom and root growth occurs here. Because this water does not circulate, slime formation takes place, which is disadvantageous for the further development of the bulb and, moreover, causes stench and rotting.

According to an alternative a tray is provided consisting of an essentially open container having a base surface from which a number of spikes or nails protrude onto which  
15 the bulbs concerned are pushed. There are thus no boundaries between the bulbs. Water is transported continuously or intermittently through a container of this type, as a result of which the problem of slime formation, stench and rotting is eliminated. The bulbs are arranged freely adjoining one another and it has been found that as a result of appreciable root formation and spread the bulbs can no longer be removed as individual items because the  
20 roots of adjacent bulbous plants become appreciably intertwined. This latter system is used in particular for long-term cultivation, for example ten weeks. The root development during such a long period can be appreciable. It is essential that the pins do not pierce through the root base because this causes irreparable damage to the plant. In practice it has been found that this does occur in particular cases.

25 According to other cultivation systems the plant is grown for a short time. Although the system of root formation described above is restricted to an appreciable extent, it is not completely eliminated. Furthermore, this means that the plant is stored dry for a longer period, as a result of which the quality could deteriorate. Moreover, the cultivation of such plants is seasonal and if the plant has to be moved again two weeks prior to harvest, this  
30 results in substantial peaks in the distribution of work, which is undesirable.

The construction described in EP 0 758 524 A1 comprises square accommodations, each of which is always provided with finger-like retaining elements half way up the boundary walls. Each tray is open at the bottom.

The aim of the present invention is to provide a plant tray with which the production of slime in the water in which the roots are standing is prevented, with which it is precluded that plants can no longer be removed because the roots of adjacent plants grow into one another and with which it is possible to carry out both a long cultivation (for example 10 weeks) and  
5 a short cultivation (for example 2 weeks).

Said aim is achieved with a plant tray as described above having the characterising features of Claim 1. Because the accommodations terminate in an opening at the bottom, a system for the supply and removal of water which is common to the various accommodations can be implemented beneath the tray, as a result of which the production of slime is no longer  
10 to be feared. Certainly in the case of long cultivation, there will be appreciable root formation and the roots of adjacent plants may grow into one another. Because of the presence of a cutting edge, when the bulb is withdrawn from the accommodations the soft root material is automatically cut free and no adjacent bulbous plants are removed at the same time.

Stable positioning of the bulbous plants in the accommodations can be promoted by  
15 fitting clamping means. A wide variety of types of clamping means are proposed in the prior art. According to an advantageous embodiment of the invention, said clamping means, however, consist of plates which preferably extend perpendicularly to the periphery of the accommodations and delimit a tapered opening for such a bulbous plant. That is to say, the bulbous plant can be pushed firmly into the clamping means. No damage to the bulbs during  
20 further growth has been observed, such as has been found in the case of systems with which the roots are skewered on pins and the like. Fixing of the bulbs is facilitated if such plates are provided with a sharp cutting edge. It is true that there is local cutting into the coat of the bulb as a result, but in general no damage to the base of the bulb takes place. The consequences of damage to the coat are less than those of damage to the base of the bulb. In cases where  
25 damage does have an adverse effect, the edges of the plates can have been chamfered. Moreover, it is possible to fix the plates only at the top or bottom of the tray, as a result of which the plates are able to move resiliently to and fro. Moreover, means can be fitted to determine the depth at which the bulbs have to be introduced over the plates, so that all bulbs are at the same height.

30 According to a further advantageous embodiment of the invention, the accommodations are made hexagonal and arranged in a honeycomb pattern. It has been found that optimum utilisation of the surface area of the tray is obtained in this way. With an embodiment of this type the clamping plates preferably extend from one or more of the

corners of the hexagons.

The wall thickness of the trays and more particularly close to the cutting edge is preferably between 0.5 and 2.5 mm. In this way adequate strength is combined with the ability to cut the relatively soft root material. The actual cutting edge of the plates is preferably made thinner and is less than 2.5 mm.

As indicated above, the invention does not relate exclusively to tulip bulbs, but other plants, such as hyacinths and narcissi, can also be cultivated using the invention.

The plant tray described above is preferably used in combination with a cultivation system with which it is ensured that the roots of the bulbs come into contact with water. This means that a water level must be chosen as a function of the depth to which the bulbs are pressed into the trays. Preferably, the various features are implemented in such a way that the tray is placed in a container into which water is introduced, which water circulates continuously or periodically. Optionally, an ebb/tide system can be used.

The invention will be explained in more detail below with reference to an illustrative embodiment shown in the drawing. In the drawing:

Fig. 1 shows a plan view of a tray according to the invention;

Fig. 2 shows a partially exposed side view of a detail of the tray according to Fig. 1; and

Fig. 3 shows a cross-section along the line 3 - 3 in Fig.1 in combination with a cultivation system and

Fig. 4 shows, diagrammatically, in cross-section, an alternative method for clamping the bulbous plant.

Fig. 1 shows a plan view of a tray for cultivating tulip bulbs. This tray is indicated by 1. The dimensions of this tray are approximately 60 x 40 cm, but it must be understood that such dimensions are not of essential importance for the inventive concept. 90 - 150 accommodations for holding tulip bulbs have, for example, been made in the tray. This number will be different for other plants.

The accommodations are indicated by reference numeral 2 and are hexagonal, the walls being indicated by 3. One accommodation is shown in detail in Fig. 2 and it can be seen that said accommodation is also provided with clamping plates 4, which are constructed such that they slope downwards at an angle, as well as with peripheral walls 3. The bottom edges of the accommodations 2 are indicated by 5. The clamping plates 4 are provided with cutting edges 12 and the edges have been made relatively sharp.

Fig. 3 shows a combination of trays 1 with an ebb/tide system. The latter consists of a liquid-tight container provided with a water feed 10 and water discharge 11, the water level at the particular point in time being indicated by 9. The tray and/or the containers are provided with spacers. The plant is indicated by 6 and it can be seen from the drawing that the roots thereof are in the water 9. By this means optimum growth of the plant can be achieved. Slime formation and rotting is prevented by regular or continuous circulation of water 9. Crop protection agents, fertilisers and the like can optionally be added to the water.

As can be seen from Fig. 3, the roots of adjacent plants 6 will become intertwined, certainly if relatively long cultivation over a number of weeks is used. Under normal circumstances this would impede the removal of the plant 6 from the accommodation 2 concerned. Because of the presence of cutting edges 5, however, the relatively soft root tissue can be simply cut through on exerting a pull on plants 6. Because the root tissue is relatively soft, the requirements in respect of the "sharpness" of cutting edge 5 are not too stringent and such a cutting edge can easily be produced directly by injection moulding with conventional chamfering.

The plant, and more particularly the bulb thereof, is clamped between the clamping plates or clamping walls 4. By this means, on the one hand, severe damage is prevented and, on the other hand, adequate fixation is ensured, so that transport and further handling of the tray are possible. The cutting edge indicated by 12 is, in particular, made sharp so that simple clamping is achieved and possible damage is restricted to a very small region. It is possible for the clamping plates to be of stepped construction or constructed in another way in order to provide a height stop for the bulbs.

A variant of the tray according to the invention is shown in Fig. 4. The components which correspond to those in Figs 1 - 3 have been provided with the same reference numerals. The clamping plates in this embodiment have been indicated by 14 and consist of strips of material fixed only at the top of walls 3. By means of this method of fixing, the plant can be resiliently clamped. In such a case it is not necessary for the edge indicated by 15 to be sharp. This edge is now made chamfered, so that no cutting into the bulb to be placed in the tray takes place.

It must be understood that such a chamfered edge 15 can also be used with the embodiment shown previously, whilst the construction described above with sharp edge 12 can be used in the embodiment under consideration.

Those skilled in the art will understand that the above tray can be modified in a number

of obvious ways. Such modifications are considered to fall within the scope of the present claims.

Claims

1. Plant tray, comprising a plastic body having a number of accommodations (2) for plants (6), wherein, in the use position, each accommodation is provided at the top with an insertion opening for the plant and is at least partially open at the bottom, characterised in that the opening at the bottom is delimited by a cutting edge (5) acting in the direction in which the plant is removed from the accommodation.
2. Plant tray according to Claim 1, comprising clamping means (4, 14) for the plant in each accommodation.
3. Plant tray according to Claim 2, wherein said clamping means comprise plates extending increasingly further into said accommodation from the insertion opening to the bottom of the accommodation.
4. Plant tray according to Claim 3, wherein said plates are essentially perpendicular to the peripheral boundary of said accommodation.
5. Plant tray according to one of Claims 2 - 4, characterised in that said clamping means (4) are provided with sharp cutting edges (12).
6. Plant tray according to one of Claims 2 - 5, comprising at least three clamping means per accommodation.
7. Plant tray according to one of the preceding claims, wherein said clamping means (14) are fitted such that they are resilient with respect to said accommodations.
8. Plant tray according to one of the preceding claims, wherein said accommodations are made hexagonal.
9. Plant tray according to Claims 6 - 8, wherein said clamping means always extend from a corner point of said hexagon.
10. Plant tray according to one of the preceding claims, wherein said boundary walls of said accommodation have a wall thickness of less than 2.5 mm.
11. Plant tray according to one of the preceding claims, wherein said accommodation is designed to take a tulip bulb.
12. Cultivation system comprising a plant tray according to one of the preceding claims, having a container (8) which takes said plant tray, wherein free space is delimited between the bottom of the tray and the base of the container.
13. Cultivation system, according to Claim 12, wherein said free space is common to at least a number of said accommodations at the bottom.



fig-1

1/2





fig-2



2/2  
fig - 3





fig - 4



DERWENT-ACC-NO: 2000-117084

DERWENT-WEEK: 200316

COPYRIGHT 2007 DERWENT INFORMATION LTD

TITLE: Tray and cultivation system for plant bulbs

INVENTOR: SMAK, P W J; SMAK, P

PATENT-ASSIGNEE: GEBR SMAK & ZN VOF[SMAKN] , HYDROPONICS HOLDING BV[HYDRN]

PRIORITY-DATA: 1998NL-1009527 (June 30, 1998)

PATENT-FAMILY:

PUB-NO	PUB-DATE	LANGUAGE
PAGES MAIN-IPC		
ES 2179662 T3	January 16, 2003	N/A
000 A01G 009/10		
WO 200000014 A2	January 6, 2000	E
010 A01G 009/10		
NL 1009527 C2	January 18, 2000	N/A
000 A01G 009/10		
AU 9946600 A	January 17, 2000	N/A
000 A01G 009/10		
EP 1091639 A2	April 18, 2001	E
000 A01G 009/10		
JP 2002519002 W	July 2, 2002	N/A
016 A01G 031/00		
EP 1091639 B1	August 28, 2002	E
000 A01G 009/10		
DE 69902666 E	October 2, 2002	N/A
000 A01G 009/10		

DESIGNATED-STATES: AE AL AM AT AU AZ BA BB BG BR BY CA CH CN CU CZ DE  
DK EE ES  
FI GB GD GE GH GM HR HU ID IL IN IS JP KE KG KP KR KZ LC LK LR LS LT  
LU LV MD  
MG MK MN MW MX NO NZ PL PT RO RU SD SE SG SI SK SL TJ TM TR TT UA UG  
US UZ VN  
YU ZA ZW AT BE CH CY DE DK EA ES FI FR GB GH GM GR IE IT KE LS LU MC  
MW NL OA  
PT SD SE SL SZ UG ZW AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU MC  
NL PT SE  
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU MC NL PT SE

APPLICATION-DATA:

PUB-NO APPL-DATE	APPL-DESCRIPTOR	APPL-NO
ES 2179662T3 June 30, 1999	N/A	1999EP-0929969
ES 2179662T3 N/A	Based on	EP 1091639
WO 200000014A2 June 30, 1999	N/A	1999WO-NL00405
NL 1009527C2 June 30, 1998	N/A	1998NL-1009527
AU 9946600A June 30, 1999	N/A	1999AU-0046600
AU 9946600A N/A	Based on	WO 200000014
EP 1091639A2 June 30, 1999	N/A	1999EP-0929969
EP 1091639A2 June 30, 1999	N/A	1999WO-NL00405
EP 1091639A2 N/A	Based on	WO 200000014
JP2002519002W June 30, 1999	N/A	1999WO-NL00405
JP2002519002W June 30, 1999	N/A	2000JP-0556610
JP2002519002W N/A	Based on	WO 200000014
EP 1091639B1 June 30, 1999	N/A	1999EP-0929969
EP 1091639B1 June 30, 1999	N/A	1999WO-NL00405
EP 1091639B1 N/A	Based on	WO 200000014
DE 69902666E June 30, 1999	N/A	1999DE-0602666
DE 69902666E June 30, 1999	N/A	1999EP-0929969
DE 69902666E June 30, 1999	N/A	1999WO-NL00405
DE 69902666E N/A	Based on	EP 1091639
DE 69902666E N/A	Based on	WO 200000014

INT-CL (IPC): A01G009/02, A01G009/10 , A01G031/00 , A01G031/02

ABSTRACTED-PUB-NO: WO 200000014A

BASIC-ABSTRACT:

NOVELTY - The tray has a series of walls (3) which form hexagonal pockets into which the bulbs are inserted. The bulbs are held in position by angled clamping plates (4) which have sharp edges (12).

USE - In the cultivation of bulbs.

ADVANTAGE - The tray layout optimises use of its surface area. The bulbs are held securely in place and the root material is cut free when the bulbs are removed.

DESCRIPTION OF DRAWING(S) - The drawing shows a cut-away side view of the tray

Walls 3

Plates 4

Edges 12

CHOSEN-DRAWING: Dwg.2/4

TITLE-TERMS: TRAY CULTIVATE SYSTEM PLANT BULB

DERWENT-CLASS: P13

SECONDARY-ACC-NO:

Non-CPI Secondary Accession Numbers: N2000-088650